

**Technical Data Sheet****Flux-Off® No Clean “Plus”  
Flux Remover****PRODUCT DESCRIPTION**

Flux-Off® No Clean “Plus” Flux Remover is an extra strength nonflammable solvent that removes heavy and encrusted flux deposits. This high pressure aerosol or bulk liquid penetrates quickly to remove all types of flux, oxide particles, dust, grease and oil, then evaporates quickly leaving no residues.


- Powerful cleaner removes R, RA, RMA, and No Clean fluxes
- Non-corrosive, safe for metals
- Flammable
- Extra-strength
- Fast drying
- Removes encrusted, baked-on fluxes
- All-Way Spray valve - even sprays upside down
- BrushClean™ System for scrubbing tough soils

**TYPICAL APPLICATIONS**

Flux-Off® No Clean “Plus” Flux Remover effectively cleans flux residues from:

- Chip Carriers
- Heat Sinks
- Metal Housings and Chassis
- Printed Circuit Boards
- Plugs
- Relays and Contacts
- Sockets
- Surface Mount Device Pads
- Solenoids
- Switches

**TYPICAL PRODUCT DATA AND  
PHYSICAL PROPERTIES**

<b>Flash Point</b>	-20°F
<b>Evaporation Rate (butyl acetate=1)</b>	>1
<b>Specific Gravity</b>	0.706
<b>Appearance</b>	Clear, Colorless Liquid
<b>Odor</b>	Ethereal
<b>Solubility in Water</b>	Negligible
<b>Kauri-Butanol (KB) Number</b>	86
<b>Shelflife</b>	5 years
<b>RoHS/WEEE Status</b>	

**COMPATIBILITY**

Flux-Off® No Clean “Plus” Flux Remover, like any cleaner, should be tested on a non-critical area to determine plastics compatibility prior to use. Not recommended for ABS, acrylics, polycarbonates, polystyrenes and PVC.

<u>Material</u>	<u>Compatibility</u>
ABS	Non-Compatible
Buna-N	Non-Compatible
EPDM	Excellent
Graphite	Excellent
HDPE	Excellent
LDPE	Good
Lexan™	Non-Compatible
Neoprene	Fair
Noryl®	Non-Compatible
Nylon™ 66	Excellent
Cross-Linked PE	Excellent
Polypropylene	Excellent
Polystyrene	Non-Compatible
PVC	Non-Compatible
Silicone Rubber	Non-Compatible
Teflon™	Excellent
Viton™	Non-Compatible

**TECHNICAL & APPLICATION ASSISTANCE**

ITW Chemtronics® provides a technical hotline to answer your technical and application related questions. The toll free number is: **1-800-TECH-401**.

**ENVIRONMENTAL IMPACT DATA**

ENVIRONMENTAL IMPACT DATA			
CFC	0.0%	VOC	51%
HCFC-141b	0.0%	HFC	0.0%
HCFC-225	0.0%	nPB	0.0%

CFC, HCFC-225, HCFC-141b, VOC, HFC, and nPB percentages shown are the content by weight.

**NOTE:**

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. ITW CHEMTRONICS® does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

**MANUFACTURED BY:**  
**ITW CHEMTRONICS**  
**8125 COBB CENTER DRIVE**  
**KENNESAW, GA 30152**

1-770-424-4888 REV. B (06/06)

Flux-Off® and Chemtronics® are registered trademarks of ITW Chemtronics. All rights reserved. BrushClean™, is a trademark of ITW Chemtronics. All rights reserved.

**USAGE INSTRUCTIONS**

For industrial use only.  
 Read MSDS carefully prior to use.  
 Spray 4-6" from surface to clean or attach brush to scrub tough soils while flushing with solvent to loosen and remove residues. Rinse parts from top to bottom, allowing the liquid to flush away flux residue.

**AVAILABILITY**

ES896BE BrushClean™ System 200 ml

**DISTRIBUTED BY:**